



IP68


CRI>70


25k/h

FOCO DE PARED MIZU

REFERENCIA	POTENCIA (W) POWER	LÚMENES LUMENS	Tª COLOR (K) COLOR T.
EC8586	20	1.900	3.500 ±5%
EC8587	20	1.950	6.000 ±5%
EC8588	20	780	RGB
EC3178	DRIVER POOL 60 VAC 12V		
EC3179	DRIVER POOL 120 VAC 12V		
EC8593	MANDO MIZU		
EC8597	RECEPTOR MIZU 150W (TUYA)		
EC8592	NICO MIZU PAR 56 ULTRA FINO		

CARACTERÍSTIAS ÓPTICAS PHOTOMETRIC DATA

CRI	>70
Temp.	3.500K / 6.000K / RGB
Lúmenes Lumens	95 lm/ W

CARACTERÍSTIAS ELÉCTRICAS ELECTRICAL DATA

Potencia Power	20 W
Tensión Voltage	AC 12 V
Frecuencia Frequency	50 - 60 Hz
Factor de potencia Power Factor	>0,90

CARACTERÍSTIAS TÉCNICAS TECHNICAL DATA

Material	Plástico
Protección IP IP Process	68
Temp. de trabajo	-20°C a 40°C
Humedad de trabajo	10 - 80%
Vida Útil Lifetime	25.000h
Chip	Epistar
Garantía Warranty	5 años / years

GRÁFICOS GRAPHICS

